

## BIS Podkładki płaskie

(K 45 30)

653



## Zalety i właściwości

- zgodne z EN-ISO 7089 ( DIN 125A)
- materiał: stal

- ocynkowane elektrolitycznie
- testowane pod względem bezpieczeństwa pożarowego

| Nr kat.   | Typ         | B<br>(mm) | s<br>(mm) | d1<br>(mm) | Pud. | Kart. |
|-----------|-------------|-----------|-----------|------------|------|-------|
| 653 3 006 | EN-ISO 7089 | 12        | 1,6       | Ø 6,4      | 100  | 2,500 |
| 653 3 008 | EN-ISO 7089 | 16        | 1,6       | Ø 8,4      | 100  | 2,500 |
| 653 3 010 | EN-ISO 7089 | 20        | 2,0       | Ø 10,5     | 100  | 2,500 |
| 653 3 012 | EN-ISO 7089 | 24        | 2,5       | Ø 13,0     | 100  | 2,500 |
| 653 3 016 | EN-ISO 7089 | 30        | 3,0       | Ø 17,0     | 50   | 2,500 |
| 653 3 020 | EN-ISO 7089 | 37        | 3,0       | Ø 21,0     | 100  | -     |

Od Ø 10,5 testowane pod względem bezpieczeństwa pożarowego.

